



700MC



Model	700MC	
Signal System	NTSC	PAL
Image Sensor	1/3" Sony Super HAD CCD II (ICX810+Sony4140)	
Total Pixels	1020 (H)X508(V)	1020 (H)X596(V)
Effective Pixels	976 (H) X494(V)	976 (H) X582(V)
Resolution	700 TV Lines	
SNR	> 50 dB (AGC Off)	
Min. Illumination	0.01 Lux @ F1.2	
Video Output	1.0Vp-p/75Ω	
Lens	Pinhole 3.7 mm	
White Balance	ATW/PUSH/ANTI-CR/USER	
Day & Night	AUTO/COLOR/BW	
Backlight	Backlight Compensation / OFF / Highlight Compensation	
D-WDR	ATR ON/OFF	
DNR	2D Y / C / Y+C	
Image adjustment	Brightness/contrast/sharpness/gain/mirror	
Motion Detection	ON/OFF (SELECT)	
Privacy Masks	ON/OFF(4 AREA)	
Language	English, Spanish, German, French, Portuguese, Russian, Japanese, Chinese	
AGC	x0.25/x0.50/x0.75/x1.00	
Electronic Shutter	1/60 - 1/10000	1/50 - 1/10000
Tilt Adjusting	+/-180 Degree	
Input Voltage	12 VDC	
Power Consumption	150mA max	
Operation Temperature	-10°C (14°F)~ +50°C (122°F)	
Storage Temperature	-20°C (-4°F) ~ +60 °C (140°F)	
Dimension	36mm (w) x 36mm (H) x 20 mm (D)	
Weight	0.09 Kg / 0.2 Lb	

