

Mini

IR 4-in-1 1080P with 10x /20x/30x optical zoom and 32x digital zoom

h l do d dphwh

Model No.		□ □ □	□ □	□ □ □ □	□ □ □ □	
		SDH716IRMF-10x		SDH716IRMF-20x		SDH716IRMF-30x
Camera	Sensor	1/2.8" Sony Starvis CMOS sensor				
	Resolution	AHD/TVI/CVI output: 1080P, Analog: 700TVL				
	Zoom Ratio	10x Optical zoom, 32x digital zoom		20x Optical zoom, 32x digital zoom		30x Optical zoom, 32x digital zoom
	Focal Length	f=5.1(Wide) – 51(Tele)mm		f=4.9(Wide) – 98(Tele)mm		f=4.3(Wide) – 129(Tele)mm
	Iris	F=1.6(Wide)-1.8(Tele)		F=1.5(Wide)-3.0(Tele)		F=1.6(Wide)-5.0(Tele)
	Mini Illumination	Color:0.2Lux, BW:0.05Lux; Color DSS:0.002Lux,BW DSS:0.001Lux				
	Day/Night	Auto/Day/Night				
	Focus	Manual/Auto / One Push				
	Iris	Auto/Manual				
	Shutter Speed	1/30(25) sec ~ 1/300,000 sec				
	DIS	OFF/10%/20%/30%				
	White Balance	Auto/Indoor/Outdoor/Manual				
	Mirror	None/Horizontal/Vertical/Horizontal& Vertical				
	HLC/WDR/BLC	On/Off				
	Defog	Auto / Off / Low / Middle / High				
	Privacy Mask	8 privacy masks programmable				
PTZ Function	Pan/Tilt Range	Pan:360°endless, Tilt: 0~90°				
	Speed	Max.300 °/sec (proportional to zoom ratio)				
	Preset	Up to 255				
	Auto Scan	8				
	Pattern	8				
	Group	8				
	RS 485	Yes				
Other PTZ Functions	Auto Flip, Parking Action, Auto protocol identification,Power up Action					
IR Function	IR radiation distance	Approximately 70m				
	Infrared mode	Auto/ Manual/ Semi-Auto				
	IR LED layout	IR LED for Near:3; Middle:6; Far:3;12 LEDs in total.				
	IR LED power	Each max. 3W				
	IR LED current	1A				
General	Dimension	Main unit without mount bracket: Φ132mm*210mm				
	Net Weight	1.5 Kg(Only PTZ dome, without mount bracket)				
	Gross Weight	1.7Kg (with wall mounting bracket)				
	Working Temp.	-20°C ~ +50°C;				
	Working Humidity	90% (Non-condensing)				
	Power Supply	DC12V				
	Power Consumption	DC12V: 33W Max.				
	IP Rating	IP 66				
	Protection Grade	Power 4000V				
Certificate	CE, FCC					